

PL-TR-93-2126

AD-A269 897



2

**A COMPARISON OF SINGLE-STATION  
BACKAZIMUTH ESTIMATES WITH REGIONAL  
EVENT LOCATIONS IN THE CENTRAL  
APPALACHIANS**

Martin C. Chapman  
Shaosong Huang  
J. Arthur Snoke

Virginia Polytechnic Institute  
and State University  
Department of Geological Sciences  
Blacksburg, Virginia 24061-0420

30 June 1993

**DTIC**  
**S** **ELECTE** **D**  
**B** **SEP 01 1993**

Scientific Report No. 1

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED



**PHILLIPS LABORATORY**  
**Directorate of Geophysics**  
**AIR FORCE MATERIEL COMMAND**  
**HANSCOM AFB, MA 01731-3010**


**93 8 31 075**


**93-20355**




The views and conclusions contained in this document are those of the authors and should not be interpreted as representing the official policies, either expressed or implied, of the Air Force or the U.S. Government.

This technical report has been reviewed and is approved for publication.

  
JAMES F. LEWKOWICZ  
Contract Manager  
Solid Earth Geophysics Branch  
Earth Sciences Division

  
JAMES F. LEWKOWICZ  
Branch Chief  
Solid Earth Geophysics Branch  
Earth Sciences Division

  
DONALD H. ECKHARDT, Director  
Earth Sciences Division

This document has been reviewed by the ESD Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS).

Qualified requestors may obtain additional copies from the Defense Technical Information Center. All others should apply to the National Technical Information Service.

If your address has changed, or if you wish to be removed from the mailing list, or if the addressee is no longer employed by your organization, please notify PL/IMA, 29 Randolph Road, Hanscom AFB MA 01731-3010. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document require that it be returned.

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 30 June 1993	3. REPORT TYPE AND DATES COVERED Scientific Report No. 1
4. TITLE AND SUBTITLE  A Comparison of Single-Station Backazimuth Estimates with Regional Event Locations in the Central Appalachians		5. FUNDING NUMBERS  F19628-92-K-0029 PE 62714E PR 2A10 TA GM WU AB
6. AUTHOR(S)  Martin C. Chapman Shaosong Huang J. Arthur Snoke		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  Virginia Polytechnic Institute and State University Department of Geological Sciences Blacksburg, Virginia 24061-0420		8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  Phillips Laboratory 29 Randolph Road Hanscom AFB, Massachusetts 01731-3010		10. SPONSORING/MONITORING AGENCY REPORT NUMBER  PL-TR-93-2126
Contract Manager: James Lewkowicz/GPEH		
11. SUPPLEMENTARY NOTES		

12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution unlimited	12b. DISTRIBUTION CODE
---	------------------------

13. ABSTRACT (Maximum 200 words)  The study examines the accuracy of single-station backazimuth measurements from polarization analysis of near regional P wave arrivals. The data set consists of 37 signals from mining explosions in the distance range 100 to 300 km, recorded at station BLA, Blacksburg, Virginia. The station-source backazimuth estimates derived from the three-component station are compared with results derived from independent information, primarily from regional network epicenter locations. For signal/noise ratios in excess of 2.0, the mean backazimuth error of the single-station estimate is 6 degrees (for sources in the northwest quadrant) and the standard deviation is 21 degrees. Generally, only the initial (1 second or less) portion of the P wave arrival is polarized in the source-station azimuth. Off-azimuth arrivals consisting of converted and scattered energy appear early in the P coda. Emergent P wave arrivals from the delay-fired explosions, combined with steep apparent angles of incidence (averaging 22 degrees) complicate the single-station, three-component location problem.	
--	--

14. SUBJECT TERMS  Source-receiver backazimuth measurement, P-wave polarization		15. NUMBER OF PAGES 52
		16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT  Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE  Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT  Unclassified
20. LIMITATION OF ABSTRACT  SAR		

# Table of Contents

<u>Section</u>	<u>Page</u>
Summary.....	vii
1. Introduction.....	1
2. The Blacksburg Three-Component Station.....	1
2.1 Calibration.....	1
3. The Regional Network.....	2
4. Location and Characteristics of the Mining Explosions.....	2
5. Method of Polarization Analysis.....	9
6. Data Analysis.....	10
7. Results.....	14
8. Conclusions.....	34
9. References.....	35

DTIC COPY NOT RECOMMENDED 1

on For	
MA&I	<input checked="" type="checkbox"/>
Used	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

## List of Illustrations

<u>Figure</u>	<u>Page</u>
1. Network stations (including three-component station BLA) are shown by circles. Crosses indicate mine locations yielding multiple explosion signals. Mines for which only a single explosion was recorded are shown by triangles.....	3
2. Confirmed mine locations are shown by the circles. Location of station BLA shown by the triangle.....	7
3. Confirmed mine locations are shown by the circles with associated letters as listed in Table 1. The location of the three-component station is shown by the triangle.....	8
4. Time series data for Explosion #16 at the Starfire Mine in Kentucky.....	11
5. Fourier amplitude spectra of the vertical component P wave arrival, Explosion #16 (solid line), and the pre-P wave noise (dashed).....	12
6. Results of polarization processing for Explosion #16.....	13
7. Three-component station backazimuth error versus signal/noise ratio.....	15
8. Three-component station backazimuth error versus rectilinearity.....	15
9. Time series data for Explosions #35 at the Central Ohio Mine.....	16
10. Time series data for Explosion #20 at the Central Ohio Mine.....	16
11. Fourier amplitude spectrum, Explosion #35: Vertical component P wave arrival (solid) and pre-P wave noise (dashed).....	17

12.	Fourier amplitude spectrum, Explosion #20: Vertical component P wave arrival (solid) and pre-P wave noise (dashed).....	17
13.	Results of polarization processing for Explosion #35.....	18
14.	Results of polarization processing for Explosion #20.....	19
15.	Apparent angle of incident P wave versus three-component signal/noise ratio.....	21
16.	Time series data for Explosion #9.....	22
17.	Fourier amplitude spectrum, Explosion #9: Vertical component P wave arrival (solid) and pre-P wave noise (dashed).....	23
18.	Results of polarization processing for Explosion #9.....	24
19.	Time series data for Explosion #12.....	25
20.	Fourier amplitude spectrum, Explosion #12: Vertical component P wave arrival (solid) and pre-P wave noise (dashed).....	26
21.	Results of polarization processing for Explosion #12.....	27
22.	Time series data for Explosion #17.....	28
23.	Fourier amplitude spectrum, Explosion #17: Vertical component P wave arrival (solid) and pre-P wave noise (dashed).....	29
24.	Results of polarization processing for Explosion #17.....	30
25.	Time series data for Explosion #33.....	31
26.	Fourier amplitude spectrum, Explosion #33: Vertical component P wave arrival (solid) and pre-P wave noise (dashed).....	32
27.	Results of polarization processing for Explosion #33.....	33

## Summary

The objective of this study is determination of the accuracy with which the station-source backazimuth can be determined from single station, three-component data in the case of industrial explosions at near regional distance. The single station backazimuth, derived from the polarization of the P wave, was a parameter reported by U.S. stations during the GSETT-2 experiment. One of these stations (BLA), located at Blacksburg, Virginia, is situated to record numerous large mining explosions in the distance range 100 to 300 km. The explosions can be reliably located using arrival time data from a regional network.

A moving window polarization analysis of the explosion P wave arrivals was performed. In a fashion similar to the procedures followed during the GSETT-2 experiment, maximum rectilinearity of motion was used as a criterion for judging the "best" backazimuth estimate from the three-component P wave data. The resulting best estimate backazimuth is compared with that derived from the independently located mines.

The results of the comparisons, performed to date on 37 signals, show that three-component signal/noise ratios less than 2.0 can result in very unreliable backazimuths. However, for 35 signals with S/N ratios exceeding 2.0, the mean backazimuth error is 6 degrees with standard deviation 21 degrees. The error in the

determinations does not appear to be strongly correlated with signal/noise ratios in the range 2 to 10.

Characteristics of the signals which contribute to the errors in the single-station backazimuth estimates include:

1. Very emergent initial motions from the delay-fired explosions.
2. Off-azimuth P wave arrivals and/or converted phases arriving very early in the P wave coda.
3. Steep apparent angles of incidence, averaging 22 degrees from vertical, which tend to reduce the signal/noise ratios on the horizontal components.

Optimum data segments for reliable source backazimuth estimates are restricted to very short time intervals (1 second or less) beginning with the initial P wave motion.



## 1. Introduction

As part of the GSETT-2 experiment, a high-quality six-channel (three component short-period and broadband) seismic system was installed at Blacksburg, Virginia, in January, 1990. The Blacksburg location is well situated to record industrial explosions in the distance range 100 to 300 km arising from surface coal mining operations in Ohio, West Virginia and Kentucky.

This report examines the accuracy with which the source-station backazimuth can be determined at station BLA from polarization analysis of the mining explosion generated P-wave signals. As a basis for the accuracy assessment, the backazimuths derived from the three component analysis at BLA are compared with the locations of the mines estimated using arrival time data recorded at stations of the Virginia Tech and Tennessee Valley Authority regional seismic networks.

## 2. The Blacksburg Three-Component Station

The Blacksburg, Virginia, GSETT-2 station was installed in January, 1990 in the WWSSN vault on the campus of Virginia Tech. This vault is founded on Cambrian dolomite of the Appalachian Valley and Ridge geologic province. The station is equipped with Teledyne Geotech GS-13 short-period and BB-13 broadband sensors. Digitization, multiplexing and calibration are performed by a Teledyne-Geotech RDAS-200 unit, and time synchronization is obtained via a Kinometrics, Inc. Omega receiver/clock. The short-period and broadband sample rates are 40 and 10 samples/sec, respectively. The data are demultiplexed, event-detected and archived by a Science Horizons, Inc. NOMAD workstation.

### 2.1 Calibration

Relative differences in system response on the two horizontal components result in systematic errors in backazimuth estimates.

Hence, the system responses of the short-period channels were determined.

The RDAS-200 unit provides for the capability of either pulse-type transient or sinusoidal steady state calibration test signals to be applied to the sensor calibration circuits. The transient calibration pulses were used to determine the short-period system response using the approach described by Chapman et al. (1988). Essentially, the method fits an ideal damped oscillator amplitude response to the Fourier amplitude spectrum of a recorded system calibration pulse. A nonlinear least squares algorithm is used to estimate the system period, damping and gain.

The amplitude responses of the horizontal channels were found to differ by less than 2 percent in the 1 to 10 Hz frequency band. The vertical component response differs from that of the two horizontals by approximately 9 percent. These differences were removed by mathematical correction of the recorded data.

### 3. The Regional Network

The network stations used to determine the locations of mining explosions are shown in Figure 1. The six stations in western Virginia and in West Virginia are operated by Virginia Tech, whereas the stations in Tennessee and Kentucky are part of a network operated by the Tennessee Valley Authority (TVA). The Virginia Tech stations are recorded digitally in an event triggered mode. The TVA stations are recorded on 16 mm Develocorder photographic film.

### 4. Location and Characteristics of the Mining Explosions

Figure 1 shows the locations of 37 mining explosions processed to date. Examination of the signals using trace overlays recorded by the Virginia Tech network indicates that the data set consists of multiple explosions at nine mine sites plus single explosions at nine additional sites. Confirmation of the geographic locations of the

explosions through contact with the mine operators has been achieved for three mines. These three confirmed locations are the Central Ohio Mine in southeastern Ohio, the Ruffner Mine in West Virginia and the Starfire Mine in eastern Kentucky, shown in Figure 2.

The epicenters of the explosions were located using the combined Virginia Tech and TVA network arrival time data (both P and S-Lg arrival times). The location program HYPOELLIPSE (Lahr, 1980) was used with a three layer crustal velocity model (Bollinger et al., 1980). The network locations and location quality estimates are given in Table 1. In cases where the event epicenter was not known from independent information and where multiple events were recorded from the same location, the network location with smallest statistical uncertainty was adopted as the epicenter of the group of explosions.




Figure 1. Network stations (including three-component station BLA) are shown by circles. Crosses indicate mine locations yielding multiple explosion signals. Mines for which only a single explosion was recorded are shown by triangles.

Table 1

EVENT NO.	Mine <sup>1</sup>	LAT (Deg. N)	LONG (Deg. W)	ERH <sup>2</sup> (km)	DIST (km)	BAZ (Deg.)	BAZ (Est)	RECT	S/N
20	A	39.80	81.69	-	308	339	334	0.88	1.1
21	A	39.80	81.69	-	308	339	368	0.91	1.4
31	A	39.80	81.69	-	308	339	20	0.93	1.7
35	A	39.80	81.69	-	308	339	239	0.87	1.7
36	A	39.80	81.69	-	308	339	331	0.89	2.2
10	B	37.43	83.12	-	241	277	275	0.99	3.0
13	B	37.43	83.12	-	241	277	250	0.98	7.2
16	B	37.43	83.12	-	241	277	270	0.96	7.2
28	B	37.43	83.12	-	241	277	289	0.97	4.1
44	B	37.43	83.12	-	241	277	243	0.97	3.8
15	C	37.80	81.81	-	139	298	248	0.94	6.1
47	C	37.80	81.81	-	139	298	271	0.98	3.8
19	-	38.53	80.39	15	146	1±4.2	357	0.88	1.8
22	-	38.53	80.39	11	146	1±4.2	9	0.85	3.2
12	-	38.13	82.40	7	202	301±1.5	299	0.98	6.9
39	-	38.13	82.40	7	202	301±1.5	286	0.98	5.0
43	-	38.13	82.40	21	202	301±1.5	313	0.94	3.1
18	-	37.99	82.54	5	206	295±0.7	280	0.97	3.3
32	-	37.99	82.54	3	206	295±0.7	265	0.98	9.5
24	-	37.58	82.18	8	161	285±2.8	144	0.93	1.4
38	-	37.58	82.18	9	161	285±2.8	283	0.93	1.3
41	-	37.58	82.18	10	161	285±2.8	314	0.96	5.4

Table 1 (continued)

EVENT NO	Mine <sup>1</sup>	LAT (Deg. N)	LONG (Deg. W)	ERH <sup>2</sup> (km)	DIST (km)	BAZ (Deg.)	BAZ (Est)	RECT	S/N
17	-	38.03	81.69	9	144	309±1.6	307	0.96	4.4
42	-	38.03	81.69	9	144	309±1.6	311	0.91	2.5
34	-	38.03	81.69	5	144	309±1.6	320	0.90	2.5
27	-	37.96	81.88	14	154	303±2.1	287	0.94	3.0
33	-	37.96	81.88	7	154	303±2.1	308	0.97	8.7
8	-	38.34	82.78	17	243	302±3.6	308	0.92	2.0
9	-	37.52	82.64	99	200	280±2.3	279	0.96	4.8
11	-	38.04	82.26	11	187	300±2.2	273	0.95	3.8
14	-	37.94	82.65	6	212	293±1.1	264	0.96	6.9
25	-	37.19	81.51	12	97	269±4.5	274	0.94	3.7
26	-	37.85	82.54	7	200	292±1.7	284	0.90	3.3
29	-	38.28	82.36	4	208	305±1.0	279	0.97	7.9
37	-	38.28	81.21	6	137	330±2.2	336	0.89	2.4
40	-	38.04	82.16	19	179	304±3.7	252	0.97	3.2

<sup>1</sup>A = Central Ohio Coal Company;

B = "Starfire" Mine, eastern Kentucky;

C = "Ruffner" Mine, Arch Minerals, Inc., Yolyn, West Virginia;

- = Mine location derived from network arrival time data: not confirmed by independent information

<sup>2</sup>ERH = Horizontal error measure from location program HYPOELLIPSE.

<sup>3</sup>Errors estimated on the basis of the angles subtended by the HYPOELLIPSE 68% confidence error ellipses.

The location capabilities of the network were examined by comparing the network derived epicenter locations of the Starfire, Ruffner and Central Ohio Mines with their known locations. Figure 2 shows the HYPOELLIPSE 68% chi-square confidence regions for the horizontal projections of the hypocenter locations. Also shown in the figure are the actual locations of the three mines. The network locations for the explosions at the Starfire Mine in Kentucky and the explosions at the Ruffner Mine in West Virginia are in good agreement with the actual locations. The network location capability for the Ohio explosions is degraded because of very low signal-to-noise ratios for that more distant source.

Figure 3 shows the location error ellipses for the remaining events in the data set. With the exception of Event 9 in Kentucky, which was well recorded only by the Virginia Tech network, the error ellipse semi-major axes are all less than 25 km. The uncertainty in the network derived backazimuths must be taken into consideration in order to assess the quality of the single-station estimates. The horizontal angles subtended by the HYPOELLIPSE error ellipses as viewed from station BLA were calculated and are listed in Table 1. The maximum uncertainty, as defined by the angular extent of the error ellipse, is  $\pm 4.6$  degrees, for Event #25. This error estimate does not account for any systematic bias due to inaccuracy of the velocity model. However, this latter source of error appears to be small, for as shown in Figure 2, the calculated locations of the Starfire and Ruffner Mines are near the true mine locations.

Information obtained from the mine operators at the three mines indicates that the larger explosions usually are the result of "cast blasting," a technique which typically utilizes delay-fired, multi-row charge designs, similar to the explosions studied by Chapman et al. (1992).




Figure 2. Confirmed mine locations are shown by the circles. Location of station BLA shown by the triangle. Ellipses indicate the horizontal projections of the 68% chi-square confidence ellipsoids for blast epicenters from location program HYPOELLIPSE.




Figure 3. Confirmed mine locations are shown by the circles with associated letters as listed in Table 1. The location of the three-component station is shown by the triangle. The ellipses indicate the horizontal projections of the HYPOELLIPSE 68% chi-square confidence ellipsoids for mine locations inferred from blast epicenters.



## 5. Method of Polarization Analysis

The backazimuth estimates from the three-component BLA station were derived using the method developed by Jurkevics (1988). The processing is carried out in the time domain using a series of overlapping time windows. For each time window, a 3 x 3 data covariance matrix is formed from the auto- and cross-variances of the three components of motion. The principle axes of the polarization ellipsoid,  $(\lambda_i u_i, i = 1, 2, 3)$  for each window are determined by solving the eigenproblem for eigenvalues  $(\lambda_1, \lambda_2$  and  $\lambda_3)$  and eigenvectors  $(u_1, u_2,$  and  $u_3)$ . For P wave motion, the azimuth of propagation is estimated from the horizontal orientation of the eigenvector corresponding to the largest eigenvalue,  $u_1$ :

$$P_{azimuth} = \tan^{-1} (u_2/u_3), \quad (1)$$

where  $u_j, j = 1, 2, 3$  are the direction cosines of the eigenvector associated with the largest eigenvalue. A measure of the degree of rectilinearity of the particle motion is given by

$$R = 1 - \left( (\lambda_2 + \lambda_3) / 2\lambda_1 \right), \quad (2)$$

which is 1.0 when  $\lambda_2$  and  $\lambda_3$  are zero, for pure P wave motion. The method can be made frequency dependent by applying the analysis to narrow bandpassed time series data.

## 6. Data Analysis

The BLA short-period data were corrected for minor differences in system response of the three component channels. Frequency domain assessment of the P wave to pre-P wave signal/noise levels was made by calculating the Fourier amplitude spectrum of the P wave and pre-P wave data segments using 10 sec time windows. Explosions with signal/noise ratios less than 2 in the frequency range 1 to 10 Hz were rejected. The three component data were then bandpass filtered using a four-pole Butterworth filter with corner frequencies 1.0 and 10.0 Hz.

The duration of the moving time window used in the polarization analysis is a critical parameter for determining accurate backazimuth estimates. Its value will depend upon the bandwidth of the signal, the sample rate and the polarization characteristics of the signal. Trial and error testing showed that a window duration of 0.5 seconds generally provided the best backazimuth determination with our data set. Given the data bandwidth of 1 to 10 Hz and a sample rate of 40 samples/second, windows less than 0.5 seconds in duration gave unstable results due to the small number of sample points, whereas larger windows tended to reduce resolution because of the non-stationary polarization character of the coda immediately following the initial P wave arrival.

The polarization analysis was performed in an automated manner, with the best-estimate of the backazimuth determined on the basis of maximum rectilinearity near the time of initial P wave motion.

Examples of the various steps involved in the processing procedure are shown in Figures 4 through 6. Shown in Figure 4 are the data from Explosion #16 at the Starfire Mine, rotated into vertical, radial and transverse components. Figure 5 shows the Fourier amplitude spectra of the 10 second P wave and pre-P wave noise segments. Figure 6 shows a 5 second duration sequence of the data centered near the time of P wave onset, with continuous running estimates of backazimuth, rectilinearity and signal/noise ratio. The signal/noise quantity was calculated as the ratio of the average three-component amplitude in the 5 second moving window to the average long-term three-component amplitude using a 10 second data segment prior to P wave onset.




Figure 4. Time series data for Explosion #16 at the Starfire Mine in Kentucky. The data have been rotated into vertical (top), radial (center), and transverse (bottom) components.




Figure 5. Fourier amplitude spectra of the vertical component P wave arrival, Explosion #16 (solid line), and the pre-P wave noise (dashed). Ten second time windows were used.




Figure 6. Results of polarization processing for Explosion #16. From the top, the traces are: (1) Vertical, (2) radial, (3) transverse, (4) station-source backazimuth (deg), (5) rectilinearity, and (6) three-component signal/noise ratio. Note that for rotated components, the true backazimuth angle is 180 degrees. Vertical lines indicate time at which the rectilinearity is maximum. The duration of the moving window for polarization analysis is 0.5 seconds.

## 7. Results

The backazimuth errors, defined as the differences in the network derived estimates and the results from the three-component polarization measurements, are plotted as functions of signal/noise ratio and rectilinearity in Figures 7 and 8, respectively. Figure 7 suggests that ratios less than 2 can, but do not always, result in very unstable estimates of the polarization parameters, as evidenced by the two points with backazimuth errors in excess of 90 degrees. These two events are #35 and #24 (Table 1). Note that other examples of explosions at both of these mines, featuring similar signal/noise ratios, produced backazimuth estimates much closer to the true values. An example involves Events 35 and 20, both at the Central Ohio Mine. Figures 9 and 10 show the three-component recordings for the explosions. Figures 11 and 12 show the vertical component P wave and pre-P wave noise spectra of the two signals, and Figures 13 and 14 summarize the three-component processing results for both events. Note that the moving window backazimuth estimates near the times of P wave onset are stable at values near the true value of 180 degrees for the rotated components, in the case of Event 20 (Figure 14), whereas those for Event 35 (Figure 13) change rapidly at times near the P wave onset. Clearly, the random changes in the character of the noise may severely affect the backazimuth determination, when the signal/noise ratio is small.

Large signal/noise ratios do not guarantee accurate backazimuth estimates, at least for BLA and this mine explosion data set. Figure 7 shows no evidence for the backazimuth error to decrease with increasing signal/noise ratio, in the range 2 to 10. Deleting the two observations with errors in excess of 100 degrees results in a mean azimuth error of -6 degrees; the standard deviation is 21 degrees.




Figure 7. Three-component station backazimuth error versus signal/noise ratio.




Figure 8. Three-component station backazimuth error versus rectilinearity.




Figure 9. Time series data for Explosions #35 at the Central Ohio Mine. (Top) Vertical component, (middle) radial component, (bottom) transverse component.




Figure 10. Time series data for Explosion #20 at the Central Ohio Mine. (Top) Vertical component, (middle) radial component, (bottom) transverse component.






Figure 11. Fourier amplitude spectrum, Explosion #35: Vertical component P wave arrival (solid) and pre-P wave noise (dashed). Ten second time windows were used.




Figure 12. Fourier amplitude spectrum, Explosion #20: Vertical component P wave arrival (solid) and pre-P wave noise (dashed). Ten second time windows were used.




Figure 13. Results of polarization processing for Explosion #35. From the top, the traces are: (1) Vertical, (2) radial, (3) transverse, (4) station-source backazimuth (deg), (5) rectilinearity, and (6) three-component signal/noise ratio. Note that for rotated components, the true backazimuth angle is 180 degrees. Vertical lines indicate time at which the rectilinearity is maximum. The duration of the moving window for polarization analysis is 0.5 seconds.




Figure 14. Results of polarization processing for Explosion #20. From the top, the traces are: (1) Vertical, (2) radial, (3) transverse, (4) station-source backazimuth (deg), (5) rectilinearity, and (6) three-component signal/noise ratio. Note that for rotated components, the true backazimuth angle is 180 degrees. Vertical lines indicate time at which the rectilinearity is maximum. The duration of the moving window for polarization analysis is 0.5 seconds.

Figure 8 shows the backazimuth error plotted as a function of rectilinearity. Again, there is no tendency in this data set for the errors to decrease with increasing values of this parameter in the range 0.8 to 1.0. Thus, it appears that the P wave arrivals from some of the mine explosions are arriving from off-azimuth directions, possibly due to refraction from laterally heterogeneous velocity structure.

As a rule, the explosion data set exhibits very emergent and complex P wave arrivals. The emergent character of the signal may be due to the extended nature of the delay-fired source-time function. For example, typical large explosions at the Starfire Mine involve up to 60 separate charges, and the duration of the source time function can be in excess of 1 second (Chapman, et al., 1992). This is also the case for some of the larger explosions at the Ruffner Mine (personal communication, mine engineers) and is probably typical of most of the explosions in our data set from other mines as well. Results from the polarization analysis indicate that, in general, only the initial portion of the P wave arrival exhibits strongly rectilinear motion, which is polarized in the source-station azimuth. Off-azimuth arrivals consisting of converted and scattered energy appear at a very early stage in the coda: rarely can accurate estimates of the P wave backazimuth be obtained from portions of the coda at times greater than 1.0 second following the initial onset time. Also, as shown in Figure 15, the P wave angles of incidence with the vertical are small, averaging 22 degrees with a standard deviation of 9 degrees. This results in a reduced signal/noise ratio on the horizontal components, which is approximately one-half of the total three-component value given in Table 1. This phenomenon, which may be station dependent, tends to further reduce the accuracy of the backazimuth determination for low S/N events.




Figure 15. Apparent angle of incident P wave versus three-component signal/noise ratio.

The above complications make accurate single-station backazimuth determination a difficult problem for this delay-fired explosion data set. Figures 16 through 27 show five examples with signal/noise ratios exceeding 4 wherein the polarization analysis resulted in backazimuth estimates correct to within 10 degrees of the true value. Note that in most cases, the very early portion of the signal yielded the best estimate of the backazimuth, and that the polarization characteristics of the immediate P wave coda tend to fluctuate strongly.




Figure 16. Time series data for Explosion #9. (Top) Vertical component, (middle) radial, (bottom) transverse.




Figure 17. Fourier amplitude spectrum, Explosion #9: Vertical component P wave arrival (solid) and pre-P wave noise (dashed). Ten second time windows were used.




Figure 18. Results of polarization processing for Explosion #9. From the top, the traces are: (1) Vertical, (2) radial, (3) transverse, (4) station-source backazimuth (deg), (5) rectilinearity, and (6) three-component signal/noise ratio. Note that for rotated components, the true backazimuth angle is 180 degrees. Vertical lines indicate time at which the rectilinearity is maximum. The duration of the moving window for polarization analysis is 0.5 seconds.






Figure 19. Time series data for Explosion #12. (Top) Vertical component, (middle) radial, (bottom) transverse.

03-MAY-91 18:44:07.00 BLA sz




Figure 20. Fourier amplitude spectrum, Explosion #12: Vertical component P wave arrival (solid) and pre-P wave noise (dashed). Ten second time windows were used.




Figure 21. Results of polarization processing for Explosion #12. From the top, the traces are: (1) Vertical, (2) radial, (3) transverse, (4) station-source backazimuth (deg), (5) rectilinearity, and (6) three-component signal/noise ratio. Note that for rotated components, the true backazimuth angle is 180 degrees. Vertical lines indicate time at which the rectilinearity is maximum. The duration of the moving window for polarization analysis is 0.5 seconds.




Figure 22. Time series data for Explosion #17. (Top) Vertical component, (middle) radial, (bottom) transverse.

28-MAR-92 20:00:17.00 BLA sz




Figure 23. Fourier amplitude spectrum, Explosion #17: Vertical component P wave arrival (solid) and pre-P wave noise (dashed). Ten second time windows were used.




Figure 24. Results of polarization processing for Explosion #17. From the top, the traces are: (1) Vertical, (2) radial, (3) transverse, (4) station-source backazimuth (deg), (5) rectilinearity, and (6) three-component signal/noise ratio. Note that for rotated components, the true backazimuth angle is 180 degrees. Vertical lines indicate time at which the rectilinearity is maximum. The duration of the moving window for polarization analysis is 0.5 seconds.




Figure 25. Time series data for Explosion #33. (Top) Vertical component, (middle) radial, (bottom) transverse.




Figure 26. Fourier amplitude spectrum, Explosion #33: Vertical component P wave arrival (solid) and pre-P wave noise (dashed). Ten second time windows were used.






Figure 27. Results of polarization processing for Explosion #33. From the top, the traces are: (1) Vertical, (2) radial, (3) transverse, (4) station-source backazimuth (deg), (5) rectilinearity, and (6) three-component signal/noise ratio. Note that for rotated components, the true backazimuth angle is 180 degrees. Vertical lines indicate time at which the rectilinearity is maximum. The duration of the moving window for polarization analysis is 0.5 seconds.

## 8. Conclusions

We have compared the single-station backazimuth estimates at BLA with independently derived locations for a set of mining explosions and find that for sources in the northwest quadrant, polarization analysis of the P wave arrival gives an essentially unbiased estimate of the source direction (mean error 6 degrees), but that the scatter in the results is substantial, with a standard deviation for 35 measurements being 21 degrees.

Characteristics of the signals which contribute to the errors in the single-station backazimuth estimates include:

1. Very emergent initial motions from the delay-fired explosions.
2. Off-azimuth P wave arrivals and/or converted phases arriving very early in the P wave coda.
3. Steep angles of incidence, averaging 22 degrees from vertical, which tend to reduce the signal/noise ratios on the horizontal components.

Optimum data segments for reliable source backazimuth estimates are restricted to very short time intervals (1 second or less) beginning with the initial P wave motion.

## 9. References

- Bollinger, G. A., M. C. Chapman and T. P. Moore, (1980), Central Virginia regional seismic network: Crustal velocity structure in central and southwestern Virginia, NUREG/CR-1217, (R6, RA), U.S. NRC, Div. of Reactor Safety Res., Contract No. NRC-04-77-134, 187 pp.
- Chapman, M. C., G. A. Bollinger and M. S. Sibol, (1992), Modeling delay-fired explosion spectra at regional distances, Bull. Seism. Soc. Am., 82, pp. 2430-2447.
- Chapman, M. C., J. A. Snoke and G. A. Bollinger, (1988), A procedure for calibrating short-period telemetered seismograph systems, Bull. Seism. Soc. Am., 78, pp. 2077-2088.
- Jurkevics, A., (1988), Polarization analysis of three-component array data, Bull. Seism. Soc. Am., 78, pp. 1725-1743.
- Lahr, J. C., (1980), Hypoellipse/Vax: A computer program for determining local earthquake hypocentral parameters, magnitude and first motion pattern, U.S. Geol. Survey Open-File Report 80-59, 67 pp.

Prof. Thomas Ahrens  
Seismological Lab, 252-21  
Division of Geological & Planetary Sciences  
California Institute of Technology  
Pasadena, CA 91125

Prof. Keiiti Aki  
Center for Earth Sciences  
University of Southern California  
University Park  
Los Angeles, CA 90089-0741

Prof. Shelton Alexander  
Geosciences Department  
403 Deike Building  
The Pennsylvania State University  
University Park, PA 16802

Prof. Charles B. Archambeau  
CIRES  
University of Colorado  
Boulder, CO 80309

Dr. Thomas C. Bache, Jr.  
Science Applications Int'l Corp.  
10260 Campus Point Drive  
San Diego, CA 92121 (2 copies)

Prof. Muawia Barazangi  
Institute for the Study of the Continent  
Cornell University  
Ithaca, NY 14853

Dr. Jeff Barker  
Department of Geological Sciences  
State University of New York  
at Binghamton  
Vestal, NY 13901

Dr. Douglas R. Baumgardt  
ENSCO, Inc  
5400 Port Royal Road  
Springfield, VA 22151-2388

Dr. Susan Beck  
Department of Geosciences  
Building #77  
University of Arizona  
Tucson, AZ 85721

Dr. T.J. Bennett  
S-CUBED  
A Division of Maxwell Laboratories  
11800 Sunrise Valley Drive, Suite 1212  
Reston, VA 22091

Dr. Robert Blandford  
AFTAC/TT, Center for Seismic Studies  
1300 North 17th Street  
Suite 1450  
Arlington, VA 22209-2308

Dr. Stephen Bratt  
ARPA/NMRO  
3701 North Fairfax Drive  
Arlington, VA 22203-1714

Dr. Lawrence Burdick  
IGPP, A-025  
Scripps Institute of Oceanography  
University of California, San Diego  
La Jolla, CA 92093

Dr. Robert Burrige  
Schlumberger-Doll Research Center  
Old Quarry Road  
Ridgefield, CT 06877

Dr. Jerry Carter  
Center for Seismic Studies  
1300 North 17th Street  
Suite 1450  
Arlington, VA 22209-2308

Dr. Eric Chael  
Division 9241  
Sandia Laboratory  
Albuquerque, NM 87185

Dr. Martin Chapman  
Department of Geological Sciences  
Virginia Polytechnical Institute  
21044 Derring Hall  
Blacksburg, VA 24061

Prof. Vernon F. Cormier  
Department of Geology & Geophysics  
U-45, Room 207  
University of Connecticut  
Storrs, CT 06268

Prof. Steven Day  
Department of Geological Sciences  
San Diego State University  
San Diego, CA 92182

Marvin Denay  
U.S. Department of Energy  
Office of Arms Control  
Washington, DC 20585

Dr. Zoltan Der  
ENSCO, Inc.  
5400 Port Royal Road  
Springfield, VA 22151-2388

Prof. Adam Dziewonski  
Hoffman Laboratory, Harvard University  
Dept. of Earth Atmos. & Planetary Sciences  
20 Oxford Street  
Cambridge, MA 02138

Prof. John Ebel  
Department of Geology & Geophysics  
Boston College  
Chestnut Hill, MA 02167

Eric Fielding  
SNEE Hall  
INSTOC  
Cornell University  
Ithaca, NY 14853

Dr. Mark D. Fisk  
Mission Research Corporation  
735 State Street  
P.O. Drawer 719  
Santa Barbara, CA 93102

Prof Stanley Flatte  
Applied Sciences Building  
University of California, Santa Cruz  
Santa Cruz, CA 95064

Dr. John Foley  
NER-Geo Sciences  
1100 Crown Colony Drive  
Quincy, MA 02169

Prof. Donald Forsyth  
Department of Geological Sciences  
Brown University  
Providence, RI 02912

Dr. Art Frankel  
U.S. Geological Survey  
922 National Center  
Reston, VA 22092

Dr. Cliff Frolich  
Institute of Geophysics  
8701 North Mopac  
Austin, TX 78759

Dr. Holly Given  
IGPP, A-025  
Scripps Institute of Oceanography  
University of California, San Diego  
La Jolla, CA 92093

Dr. Jeffrey W. Given  
SAIC  
10260 Campus Point Drive  
San Diego, CA 92121

Dr. Dale Glover  
Defense Intelligence Agency  
ATTN: ODT-1B  
Washington, DC 20301

Dan N. Hagedon  
Pacific Northwest Laboratories  
Battelle Boulevard  
Richland, WA 99352

Dr. James Hannon  
Lawrence Livermore National Laboratory  
P.O. Box 808  
L-205  
Livermore, CA 94550

Prof. David G. Harkrider  
Seismological Laboratory  
Division of Geological & Planetary Sciences  
California Institute of Technology  
Pasadena, CA 91125

Prof. Danny Harvey  
CIRES  
University of Colorado  
Boulder, CO 80309

Prof. Donald V. Helmberger  
Seismological Laboratory  
Division of Geological & Planetary Sciences  
California Institute of Technology  
Pasadena, CA 91125

Prof. Eugene Herrin  
Institute for the Study of Earth and Man  
Geophysical Laboratory  
Southern Methodist University  
Dallas, TX 75275

Prof. Robert B. Herrmann  
Department of Earth & Atmospheric Sciences  
St. Louis University  
St. Louis, MO 63156

Prof. Lane R. Johnson  
Seismographic Station  
University of California  
Berkeley, CA 94720

Prof. Thomas H. Jordan  
Department of Earth, Atmospheric &  
Planetary Sciences  
Massachusetts Institute of Technology  
Cambridge, MA 02139

Prof. Alan Kafka  
Department of Geology & Geophysics  
Boston College  
Chestnut Hill, MA 02167

Robert C. Kemerait  
ENSCO, Inc.  
445 Pineda Court  
Melbourne, FL 32940

Dr. Karl Koch  
Institute for the Study of Earth and Man  
Geophysical Laboratory  
Southern Methodist University  
Dallas, Tx 75275

Dr. Max Koontz  
U.S. Dept. of Energy/DP 5  
Forrestal Building  
1000 Independence Avenue  
Washington, DC 20585

Dr. Richard LaCoss  
MIT Lincoln Laboratory, M-200B  
P.O. Box 73  
Lexington, MA 02173-0073

Dr. Fred K. Lamb  
University of Illinois at Urbana-Champaign  
Department of Physics  
1110 West Green Street  
Urbana, IL 61801

Prof. Charles A. Langston  
Geosciences Department  
403 Deike Building  
The Pennsylvania State University  
University Park, PA 16802

Jim Lawson, Chief Geophysicist  
Oklahoma Geological Survey  
Oklahoma Geophysical Observatory  
P.O. Box 8  
Leonard, OK 74043-0008

Prof. Thorne Lay  
Institute of Tectonics  
Earth Science Board  
University of California, Santa Cruz  
Santa Cruz, CA 95064

Dr. William Leith  
U.S. Geological Survey  
Mail Stop 928  
Reston, VA 22092

Mr. James F. Lewkowicz  
Phillips Laboratory/GPEH  
29 Randolph Road  
Hanscom AFB, MA 01731-3010( 2 copies)

Mr. Alfred Lieberman  
ACDA/VI-OA State Department Building  
Room 5726  
320-21st Street, NW  
Washington, DC 20451

Prof. L. Timothy Long  
School of Geophysical Sciences  
Georgia Institute of Technology  
Atlanta, GA 30332

Dr. Randolph Martin, III  
New England Research, Inc.  
76 Olcott Drive  
White River Junction, VT 05001

Dr. Robert Masse  
Denver Federal Building  
Box 25046, Mail Stop 967  
Denver, CO 80225

Dr. Gary McCartor  
Department of Physics  
Southern Methodist University  
Dallas, TX 75275

Prof. Thomas V. McEvilly  
Seismographic Station  
University of California  
Berkeley, CA 94720

Dr. Art McGarr  
U.S. Geological Survey  
Mail Stop 977  
U.S. Geological Survey  
Menlo Park, CA 94025

Dr. Keith L. McLaughlin  
S-CUBED  
A Division of Maxwell Laboratory  
P.O. Box 1620  
La Jolla, CA 92038-1620

Stephen Miller & Dr. Alexander Florence  
SRI International  
333 Ravenswood Avenue  
Box AF 116  
Menlo Park, CA 94025-3493

Prof. Bernard Minster  
IGPP, A-025  
Scripps Institute of Oceanography  
University of California, San Diego  
La Jolla, CA 92093

Prof. Brian J. Mitchell  
Department of Earth & Atmospheric Sciences  
St. Louis University  
St. Louis, MO 63156

Mr. Jack Murphy  
S-CUBED  
A Division of Maxwell Laboratory  
11800 Sunrise Valley Drive, Suite 1212  
Reston, VA 22091 (2 Copies)

Dr. Keith K. Nakanishi  
Lawrence Livermore National Laboratory  
L-025  
P.O. Box 808  
Livermore, CA 94550

Prof. John A. Orcutt  
IGPP, A-025  
Scripps Institute of Oceanography  
University of California, San Diego  
La Jolla, CA 92093

Prof. Jeffrey Park  
Kline Geology Laboratory  
P.O. Box 6666  
New Haven, CT 06511-8130

Dr. Howard Patton  
Lawrence Livermore National Laboratory  
L-025  
P.O. Box 808  
Livermore, CA 94550

Dr. Frank Pilotte  
HQ AFTAC/TT  
130 South Highway A1A  
Patrick AFB, FL 32925-3002

Dr. Jay J. Pulli  
Radix Systems, Inc.  
201 Perry Parkway  
Gaithersburg, MD 20877

Dr. Robert Reinke  
ATTN: FCTVTD  
Field Command  
Defense Nuclear Agency  
Kirtland AFB, NM 87115

Prof. Paul G. Richards  
Lamont-Doherty Geological Observatory  
of Columbia University  
Palisades, NY 10964

Mr. Wilmer Rivers  
Teledyne Geotech  
314 Montgomery Street  
Alexandria, VA 22314

Dr. Alan S. Ryall, Jr.  
ARPA/NMRO  
3701 North Fairfax Drive  
Arlington, VA 22209-1714

Dr. Richard Sailor  
TASC, Inc.  
55 Walkers Brook Drive  
Reading, MA 01867

Prof. Charles G. Sammis  
Center for Earth Sciences  
University of Southern California  
University Park  
Los Angeles, CA 90089-0741

Prof. Christopher H. Scholz  
Lamont-Doherty Geological Observatory  
of Columbia University  
Palisades, NY 10964

Dr. Susan Schwartz  
Institute of Tectonics  
1156 High Street  
Santa Cruz, CA 95064

Secretary of the Air Force  
(SAFRD)  
Washington, DC 20330

Office of the Secretary of Defense  
DDR&E  
Washington, DC 20330

Thomas J. Sereno, Jr.  
Science Application Int'l Corp.  
10260 Campus Point Drive  
San Diego, CA 92121

Dr. Michael Shore  
Defense Nuclear Agency/SPSS  
6801 Telegraph Road  
Alexandria, VA 22310

Dr. Robert Shumway  
University of California Davis  
Division of Statistics  
Davis, CA 95616

Dr. Matthew Sibol  
Virginia Tech  
Seismological Observatory  
4044 Derring Hall  
Blacksburg, VA 24061-0420

Prof. David G. Simpson  
IRIS, Inc.  
1616 North Fort Myer Drive  
Suite 1050  
Arlington, VA 22209

Donald L. Springer  
Lawrence Livermore National Laboratory  
L-025  
P.O. Box 808  
Livermore, CA 94550

Dr. Jeffrey Stevens  
S-CUBED  
A Division of Maxwell Laboratory  
P.O. Box 1620  
La Jolla, CA 92038-1620

Lt. Col. Jim Stobie  
ATTN: AFOSR/NL  
110 Duncan Avenue  
Bolling AFB  
Washington, DC 20332-0001

Prof. Brian Stump  
Institute for the Study of Earth & Man  
Geophysical Laboratory  
Southern Methodist University  
Dallas, TX 75275

Prof. Jeremiah Sullivan  
University of Illinois at Urbana-Champaign  
Department of Physics  
1110 West Green Street  
Urbana, IL 61801

Prof. L. Sykes  
Lamont-Doherty Geological Observatory  
of Columbia University  
Palisades, NY 10964

Dr. David Taylor  
ENSCO, Inc.  
445 Pineda Court  
Melbourne, FL 32940

Dr. Steven R. Taylor  
Los Alamos National Laboratory  
P.O. Box 1663  
Mail Stop C335  
Los Alamos, NM 87545

Prof. Clifford Thurber  
University of Wisconsin-Madison  
Department of Geology & Geophysics  
1215 West Dayton Street  
Madison, WI 53706

Prof. M. Nafi Toksoz  
Earth Resources Lab  
Massachusetts Institute of Technology  
42 Carleton Street  
Cambridge, MA 02142

Dr. Larry Turnbull  
CIA-OSWR/NED  
Washington, DC 20505

Dr. Gregory van der Vink  
IRIS, Inc.  
1616 North Fort Myer Drive  
Suite 1050  
Arlington, VA 22209

Dr. Karl Veith  
EG&G  
5211 Auth Road  
Suite 240  
Suitland, MD 20746

Prof. Terry C. Wallace  
Department of Geosciences  
Building #77  
University of Arizona  
Tucson, AZ 85721



Dr. Thomas Weaver  
Los Alamos National Laboratory  
P.O. Box 1663  
Mail Stop C335  
Los Alamos, NM 87545

Phillips Laboratory  
ATTN: TSML  
5 Wright Street  
Hanscom AFB, MA 01731-3004

Dr. William Wortman  
Mission Research Corporation  
8560 Cinderbed Road  
Suite 700  
Newington, VA 22122

Phillips Laboratory  
ATTN: PL/SUL  
3550 Aberdeen Ave SE  
Kirtland, NM 87117-5776 (2 copies)

Prof. Francis T. Wu  
Department of Geological Sciences  
State University of New York  
at Binghamton  
Vestal, NY 13901

Dr. Michel Bouchon  
I.R.I.G.M.-B.P. 68  
38402 St. Martin D'Herès  
Cedex, FRANCE

ARPA, OASB/Library  
3701 North Fairfax Drive  
Arlington, VA 22203-1714

Dr. Michel Campillo  
Observatoire de Grenoble  
I.R.I.G.M.-B.P. 53  
38041 Grenoble, FRANCE

HQ DNA  
ATTN: Technical Library  
Washington, DC 20305

Dr. Kin Yip Chun  
Geophysics Division  
Physics Department  
University of Toronto  
Ontario, CANADA

Defense Intelligence Agency  
Directorate for Scientific & Technical Intelligence  
ATTN: DTIB  
Washington, DC 20340-6158

Prof. Hans-Peter Harjes  
Institute for Geophysics  
Ruhr University/Bochum  
P.O. Box 102148  
4630 Bochum 1, GERMANY

Defense Technical Information Center  
Cameron Station  
Alexandria, VA 22314 (2 Copies)

Prof. Eystein Husebye  
NTNF/NORSAR  
P.O. Box 51  
N-2007 Kjeller, NORWAY

TACTEC  
Battelle Memorial Institute  
505 King Avenue  
Columbus, OH 43201 (Final Report)

David Jepsen  
Acting Head, Nuclear Monitoring Section  
Bureau of Mineral Resources  
Geology and Geophysics  
G.P.O. Box 378, Canberra, AUSTRALIA

Phillips Laboratory  
ATTN: XPG  
29 Randolph Road  
Hanscom AFB, MA 01731-3010

Ms. Eva Johannisson  
Senior Research Officer  
FOA  
S-172 90 Sundbyberg, SWEDEN

Phillips Laboratory  
ATTN: GPE  
29 Randolph Road  
Hanscom AFB, MA 01731-3010

Dr. Peter Marshall  
Procurement Executive  
Ministry of Defense  
Blacknest, Brimpton  
Reading FG7-FRS, UNITED KINGDOM

Dr. Bernard Massinon, Dr. Pierre Mechler  
Societe Radiomana  
27 rue Claude Bernard  
75005 Paris, FRANCE (2 Copies)

Dr. Svein Mykkeltveit  
NTNT/NORSAR  
P.O. Box 51  
N-2007 Kjeller, NORWAY (3 Copies)

Prof. Keith Priestley  
University of Cambridge  
Bullard Labs, Dept. of Earth Sciences  
Madingley Rise, Madingley Road  
Cambridge CB3 0EZ, ENGLAND

Dr. Jorg Schlittenhardt  
Federal Institute for Geosciences & Nat'l Res.  
Postfach 510153  
D-30631 Hannover , GERMANY

Dr. Johannes Schweitzer  
Institute of Geophysics  
Ruhr University/Bochum  
P.O. Box 1102148  
4360 Bochum 1, GERMANY

Trust & Verify  
VERTIC  
8 John Adam Street  
London WC2N 6EZ, ENGLAND